






5







		2
"_XX"		
"-XX" See Table 2	 >	

NOTES:

- 1. CABLE: 26 AWG, 19 CONDUCTOR, OD: 0.270 NOMINAL. POLYURETHANE INSULATION. OUTER SHIELD 38 AWG, TIN PLATED COPPER BRAID, 90% COVERAGE.
- 2. OVERMOLD MATERIAL: 90A POLYETHER-TYPE THERMOPLASTIC POLYURETHANE (TPU).
- 3. JACKET: BLACK MATTE FINISH.
- 4. E33,E34 IS CHASSIS GROUND
- SOLDERING IAW IPC-J-STD-001 CLASS II AS APPLICABLE.
- 6. CABLE ASSEMBLIES TO BE 100% TESTEDFOR CONTINUITY, SHORTS AND INSULATION RESISTANCE (250V @100MOHM MINIMUM)
- 7. IDENTIFICATION: BAG ANDINDENTIFY ON PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED. UOS PART MARKING ON THE WIRE IS PROHIBITED:

PN: TE-32ML-F-XX REV X (REV MARKING PER PO)

CAGE CODE: 1HJX9 DATE OF MFGR: MM/YY

- 8. WIRING FUNCTION: SEE TABLE 1 AND DRAWING SN0057.
- 9. REFERENCE SUPPLYNET FILE NUMBER SN0069.
- 10. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

BILL OF MATERIALS						
ITEM NO.	PART NUMBER	QTY	NAME	COMMENTS		
1	51234	74"	WIRE	19 C CABLE		
				INCLUDES HOUSING, FASTENERS,		
2	TE-32M-ASSY	1	CONNECTOR ASSEMBLY	THUMBWHEEL. PROVIDED BY		
				SUPPLYNET		
3	TBD	AR	SOLDER			
4	SN0057	1	PCB	SUPPLYNET PROVIDED.		

				REF.	NUM	BER:	SN00	69	
UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Cunn	hilliol		ECUTIVE BLVI	D.	
DIMENSIONS ARE IN: INCHES TOLERANCES: XX: ± 0.03	DRAWN	TC	03/11/15	anhh	IIYNCI	VALLE	D Y COTTAGE. N	Y 10989	
	CHECKED	RJB	03/11/15	TITLE:	FR <i>C</i>)VIT E)	(IT PR	_117	G
	COMMENTS:	COMMENTS:		32 PIN DATA CABLE, 6 FEE FOR VOICE/PTT/RS-323/					FEET
SUFACE FINISH: GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	PROPRIETARY THE INFORMATIO DRAWING IS THE SUPPLYNET, INC.	n Conta Sole Pro Any Repf	INED IN THIS PERTY OF RODUCTION	SIZE	DWG.	NO.	ET. J3		REV
MATERIAL: SEE DRAWING NOTES	IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC.		В	[,	32N	۱L-F	-XX		
FINISH: SEE DRAWING NOTES	IS PROHIBITED.								
DO NOT SCALE DRAWING	CAGE CO	ODE: 1	HJX9	SCAI	LE: NA	WEIGH	łT:	SHEET	1 OF 1

7 6 5 4 3 2