

NOTES:

WIRING SHALL BE DONE IN ACCORDANCE WITH TABLE 1 WIRE RUN LIST.

- MARKING REQUIREMENTS:
 - 1. LABELS SHALL BE MARKED IN ACCORDANCE WITH MIL-STD-130 AS APPLICABLE.
 - 2. LABELS SHALL BE WHITE WITH BLACK TEXT.
 - 3. LABELS SHALL BE PLACED WHERE SHOWN IN DRAWING.
 - 4. ADHESIVE WRAP-AROUND LABEL MAY BE USED.
- 5 SEE TABLE 2 FOR LABEL TEXT
- 3. SOLDERING: IAW IPC-J-STD-001 CLASS 2 AS APPLICABLE
- 4. ASSEMBLY TO BE 100% TESTED FOR SHORTS, CONTINUITY, AND JACKET RESISTANCE (250V @ 100MOHM MIN.)
- 5. PACKAGING REQUIREMENTS:
 - I. EACH COMPLETED ASSEMBLY SHALL BE PLACED IN A ZIP POLY BAG.
 - 2. EACH POLY BAG SHALL BE LABELED WITH THE BELOW INFORMATION ONLY.

PN: SN-987-5011-001REV. X (REV MARKING PER PO)

CAGE CODE: 1HJX9

MFD: MM/YY

6. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

BILL OF MATERIALS								
ITEM NO.	PART NO.	QTY	NAME/DESCRIPTION					
1	09HD15	2	HD15, FEMALE, 15 POS.					
2	0429-OM-01	2	HD15 OVER-MOLD, BLACK					
3	X-2316426PU	40.0"	CABLE: 4C, (2) AWG 26, (2) COAX, SHIELDED, PU					
			JACKET, BLACK.					
4	TBD	1.0"	ADHESIVE WRAP-AROUND LABEL					

				REF.	NUN	MBER: SN096	1		
UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Cur	nnlvN		UTIVE BLVI)	
DIMENSIONS ARE IN: INCHES	DRAWN	MOB	01/03/23	Ju	PHIN		SUITE B VALLEY COTTAGE, NY 10989		
TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005	CHECKED	RB	01/03/23	TITLE: DAGD DAGD DIGD					
ANGULAR: .X°: 1° .XX°: 0.5° BREAK EDGES: .005020 FILLETS: .005020	COMMENTS:		DAGR-DAGR, PLGR CABLE						
SUFACE FINISH:	PROPRIETARY AND CONFIDENTIAL			(NSN: 5995-01-521-2713)					
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC. IS PROHIBITED.		SIZE	DWG			REV		
MATERIAL: SEE DRAWING NOTES			B SN-987-5011-001				Α		
FINISH: SEE DRAWING NOTES							, ,		
DO NOT SCALE DRAWING CAGE CODE: 1HJX9				SCA	LE: NA	WEIGHT:	SHEE	T 1 OF 1	

7 6 5 4 3