
**TABLE 1: WIRE RUN LIST** WIRE COLORS 5 RED BLACK JUMPER WIRE 2.4

\*JUMP PIN 2 & 4

	REVISIONS					
REV.	REV. DESCRIPTION		APPROVED			
J	CHANGED DIODE TO 45V 12A	1/20/2021	MOB			
K	ADDED HI-POT NOTES, CHANGED ITEM NO . 1 PN	3/29/2022	МОВ			

	_,					
D	TABLE 2: WIRE LENGTH CHART					
	PART NUMBER & PART MARKING	"-XX" DIMENSION (INCHES)	TOLERANCE (INCHES)			
	191004F-01	12	+1.0", -0.0"			
	191004F-02	24	+2.0", -0.0"			
	191004F-03	36	+2.0", -0.0"			
	191004F-04	48	+2.0", -0.0"			
	191004F-05	60	+2.0", -0.0"			
	191004F-06	72	+4.0", -0.0"			
	191004F-08	96	+4.0", -0.0"			
	191004F-10	120	+4.0", -0.0"			
С	191004F-12	144	+6.0", -0.0"			
-	191004F-15	216	+6.0", -0.0"			
	191004F-20	240	+6.0", -0.0"			






TABLE 2: BILL OF MATERIALS					
ITEM NO.	PART NO	QTY	NAME/DESCRIPTION		
1	202C-U07A	AR	CABLE, 2C, AWG 20, PU JACKET, 4.6MM OD		
2	CONN-BA5590-MT	1	Male BA5590 with Threaded Backshell		
3	SBR12A45SD1-TDITR-ND	1	DIODE SCHOTTKY, 45V, 12A		
4	SR:0024	1	THREADED STRAIN RELIEF		

## NOTES:

- WIRE FUNCTION: SEE TABLE 1 WIRE RUN LIST.
- CABLE LENGTH "-XX" PER PO.
- ASSEMBLY TO BE 100% TESTED FOR CONTINUITY, SHORTS, AND JACKET RESISTANCE. (250V @ 100MOHM MIN)
- SOLDERING: IAW IPC-J-STD-001 CLASS II AS APPLICABLE.
- IDENTIFICATION: BAG AND IDENTIFY ON PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED.

PN: 191004E-XX REV. X ("-XX" & REV AS PER PO)

**CAGE CODE: 1HJX9** MFD: MM/YY

- REFERENCE SUPPLYNET FILE NUMBER SN0617.
- MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

REF. NUMBER: SN0617 DESIGN UNLESS OTHERWISE SPECIFIED: NAME DATE ENGINEERING LS 3/29/2019 DRAWN DIMENSIONS ARE IN: INCHES MANUFACTURING TOLERANCES: .XX: ± 0.03 RB 3/29/2019 TITLE: .XXX: ± 0.005 ANGULAR: .X°:1° CHECKED **BB-2590 BATTERY CABLE WITH** .XX°: 0.5° COMMENTS: BREAK EDGES: .005 - .020 POLYURETHANE JACKET, 24V FILLETS: .005 - .020 WITH DIODE, VARIABLE LENGTH SUFACE FINISH: PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS GEOMETRIC TOLERANCING DRAWING IS THE SOLE PROPERTY OF SIZE DWG. NO. PER: ASME Y14.5 -2009 SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLF WITHOUT THE 191004F-XX MATERIAL: SEE DRAWING NOTES WRITTEN PERMISSION OF SUPPLYNET INC. FINISH: SEE DRAWING NOTES

3

DO NOT SCALE DRAWING

CAGE CODE: 1HJX9

SCALE: NA WEIGHT: SHEET 1 OF 2

REV

D