





PLACE A DROP OF LOCTITE 495
ON END OF STRAIN RELIEF / WIRE MATE

PLACE A SMALL AMOUNT OF
LOCTITE 495 ON EACH POST PROR TO ASSEMBLY

ALL (4) POST MUST BE
INSERTED IF ANY POSTS
ARE MISSING DISCARD PART.

FILL WITH POTTING MATERIAL

UNLESS OTHERWISE SPECIFIED:			
DIMENSIONS ARE IN: INCHES	DRAWN	NAME	DATE
TOLERANCES: .XX: ± 0.03	LS	LS	4/16/2019
.XXX: ± 0.005	CHECKED	RB	4/16/2019
ANGULAR: .X*: 1°	COMMENTS:		
.XX*: 0.5°			
BREAK EDGES: .005 - .020	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC. IS PROHIBITED.		
FILLETS: .005 - .020			
SURFACE FINISH:			
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009			
MATERIAL: SEE DRAWING NOTES	CAGE CODE: 1HJX9		
FINISH: SEE DRAWING NOTES			
DO NOT SCALE DRAWING			

REF. NUMBER:		SN0424	
SupplyNet		DESIGN ENGINEERING MANUFACTURING	
TITLE:			
2-WAY 24 VDC CABLE, ISOLATED POWER, W/VELCRO STRAPS			
SIZE	DWG. NO.		REV
B	SN-333-VS2C1-06		E
SCALE: NA		WEIGHT:	SHEET 2 OF 2