

E33,E34 IS CHASSIS GROUND

SOLDERING IAW IPC-J-STD-001 CLASS II AS APPLICABLE. CABLE ASSEMBLIES TO BE 100% TESTEDFOR CONTINUITY, SHORTS AND INSULATION RESISTANCE (250V @100MOHM MINIMUM)

DENTIFICATION: BAG AND INDENTIFY ON PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED. UOS PART MARKING ON THE WIRE IS PROHIBITED:

PN: TE-32C-H-06 REV X (REV MARKING PER PO) CAGE CODE: 1HJX9 DATE OF MFGR: MM/YY

8. WIRING FUNCTION: SEE SHEET 2 TABLE 1 AND DRAWING SN0072.
9. REFERENCE SUPPLYNET FILE NUMBER SN0074.
10. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

FIFASED	: DOCUMENT	CONTROLED	PFR FR 1003

	BILL OF MATERIALS								
	ITEM NO.	NO. PART NUMBER		NAME	COMMENTS				
	1	51245	74"	WIRE	12C CABLE230 DIAMETER				
					INCLUDES HOUSING, FASTENERS,				
2	TE-32C-ASSY	1	CONNECTOR ASSEMBLY	THUMBWHEEL. PROVIDED BY					
					SUPPLYNET				
	3	24-7068-7601	AR	SOLDER, LEAD FREE	KESTER				
	4	SN0072	1	PCB	SUPPLYNET PROVIDED				

				PART NUMBER: TE-32C-H-06				
UNLESS OTHERWISE SPECIFIED:		NAME	DATE	CunnlyN		614 CORPORATE WAY SUITE 8M		
DIMENSIONS ARE IN: INCHES	DRAWN	RJB	04/02/13	Ju	וונוץץ	VALLEY COT	Y COTTAGE, NY 10989	
TOLERANCES: .XX: ±0.03 .XXX: ±0.005	CHECKED	RJB	04/02/16	TITLE:		D = =\//= DD		
ANGULAR: X : 1 ' X : 0.5' BREAK EDGES: .005020 FILLETS: .005020 SUFACE FINISH:	COMMENTS:		SIDE EXIT PRC-152 32 PIN DATA CABLE, 6 FEET J3 PORT SIZE DWG. NO. REV					
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC.						REV	
MATERIAL: SEE DRAWING NOTES			В	llĿ.	-32C-H-	-061	ΑΙ	
FINISH: SEE DRAWING NOTES IS PROHIBITED.					. –			, ,
DO NOT SCALE DRAWING	CAGE CO	DDE: 1	HJX9	SCAI	E: NA	WEIGHT:	SHEET	1 OF 2
•								

8

